2021 6000 R SX





NEW FOR 2021

- Throttle Body Injection
- Improved low end power and response
- Revised Rear Suspension
- 2" longer front torque arm for improved handling and transfer control
- Revised rail braces
- New Snow Flap with additional Roost protection

KEY FEATURES

- Fox 2.0 Zero C Front Track Shock with position sensing grooved body
- Spring designs to support the 2.0" body (optional rates available)
- 20/49 gearing with TOS slip clutch
 49 tooth bottom sprocket to
 eliminate peak spike loads
- Manual chain adjuster for optimal adjustment settings
- TS-273 TEAM driven with Lightweight Tubular Driven shaft
- Light weight ceramic coated expansion chamber
- V-Force Reeds
- Race inspired upper chassis structure giving improved ergo
- 3 Gallon lightweight Fuel tank
- Lightweight Race Body and Seat design
- Adjustable camber front suspension

	0004 / 000 P OV
	2021 6000 R SX
ENGINE	
TYPE	2-stroke Throttle Body Injection
DISPLACEMENT	599cc
COOLING	Liquid
CYLINDERS	Twin
BORE X STROKE	73.8 x 70 mm (2.906 x 2.755 in.)
LUBRICATION	Premix (40:1 ratio) Arctic Cat Synthetic C-tec2 oil
CARBURETION	47mm Throttle Body
EXHAUST	APV with tuned ceramic-coated pipe, pipe sensor and canister
COOLING SYSTEM CAPACITY	4.75 l (5.0 U.S. qt.)
STARTING SYSTEM	Manual recoil
GASOLINE	Sunoco Surge 105 Race Fuel (or equivalent)
FUEL CAPACITY	3 gal (11.4 L)
POWERTRAIN	
DRIVE CLUTCH	Arctic (rpm sensing)
DRIVEN CLUTCH	Team TS-273 Driven
CHAINCASE LUBRICANT LEVEL	443.6 ml (12 fl. oz.)
BRAKES	Race Hydraulic Cyclone Master Cylinder with 2-piece stainless disk
SUSPENSION	
SUSPENSION FRONT SUSPENSION	ARS II TM with FOX FLOAT 3® EVOL RC
	10 in. (25.4 cm)
FRONT SUSPENSION	711.0 11 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
FRONT SUSPENSION FRONT TRAVEL	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock,
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm) C&A Pro XT Skis
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL TRACK TYPE	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm) C&A Pro XT Skis SX 2.52 in. Pitch Snocross 2-ply
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL TRACK TYPE TRACK WIDTH	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm) C&A Pro XT Skis SX 2.52 in. Pitch Snocross 2-ply 15 in. (38 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL TRACK TYPE TRACK WIDTH TRACK LENGTH	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm) C&A Pro XT Skis SX 2.52 in. Pitch Snocross 2-ply 15 in. (38 cm) 136 in. (345.4 cm)
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL TRACK TYPE TRACK WIDTH TRACK LENGTH LUG	10 in. [25.4 cm] Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. [38.1 cm] 128 in. [325.1 cm] 49.25–50.25 in. [125.1–127.6 cm] 43.5 in. [110.5 cm] C&A Pro XT Skis SX 2.52 in. Pitch Snocross 2-ply 15 in. [38 cm] 136 in. [345.4 cm] 1.75 in. [4.4 cm]
FRONT SUSPENSION FRONT TRAVEL REAR SUSPENSION REAR TRAVEL DIMENSIONS OVERALL LENGTH OVERALL WIDTH SKI STANCE SKI MATERIAL TRACK TYPE TRACK WIDTH TRACK LENGTH LUG FEATURES	10 in. (25.4 cm) Slide-action Rear Suspension, FOX® 2.0 ZERO C F/T shock, 2.0 ZERO RC R/T shock 15 in. (38.1 cm) 128 in. (325.1 cm) 49.25–50.25 in. (125.1–127.6 cm) 43.5 in. (110.5 cm) C&A Pro XT Skis SX 2.52 in. Pitch Snocross 2-ply 15 in. (38 cm) 136 in. (345.4 cm) 1.75 in. (4.4 cm)



Black